


DESIGN PARAMETERS

The unit described in these drawings is engineered to adequately support the loads created by a wind velocity of 120 MPH at a height of 50' above ground using ASCE 7-95 exposure category "C". An additional 2' in height was added to the base during these calculations to account for variations in roof pitch, etc.

P.O. BOX 1340  
 HENDERSON TX 75653-1340  
 903/657-6522  
 FAX# 903/657-2318



Project: CUPOLA UNIT #1100


Date: 08-03-01  
 Revisions 11-14-05 AGT  
 Scale: 1/2"=1'

Drawing By: JC  
 Checked By:  
 File # ALL-STL\  
 DWG # CU1100F

Sheet#  
 E1F  
 ELEVATION

DOMES #802

CUPOLA UNIT #802 WITH  
 KRINKLGLAS WINDOWS  
 ROUND TOP



① ELEVATION  
 E1

THESE DRAWINGS ARE THE PROPERTY OF FIBERGLASS SPECIALTIES INC. DIMENSIONS AND DETAILS ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL CUPOLA AND STEEPLE UNITS ARE FABRICATED USING MINIMAL STANDING SEAMS UNLESS OTHERWISE NOTED. ALL CUPOLA AND STEEPLE UNITS ARE DESIGNED TO BE ERECTED ON A COMPLETED ROOFING SYSTEM AND ARE NOT GUARANTEED TO BE LEAK PROOF.