


DESIGN PARAMETERS

The unit described in these drawings is engineered to adequately support the loads created by a wind velocity of 120 MPH at a height of 50' above ground using ASCE 7-95 exposure category "C". An additional 2' in height was added to the base during these calculations to account for variations in roof pitch, etc.

P.O. BOX 1340
HENDERSON, TX 75653-1340
903/657-6522
FAX# 903/657-2318




DOME #603H

CUPOLA UNIT #603 WITH SQUARE TOP KRINKGLAS WINDOWS

BASE CUPOLA UNIT #604

1
E1 ELEVATION



Project: CUPOLA UNIT #1107

Date: 08-08-01

Revisions 11-16-05 AGT

Drawing By: JC

Checked By: ALL-STL

File # CU1107F

Scale: 3/8" = 1'

THESE DRAWINGS ARE THE PROPERTY OF FIBERGLASS SPECIALTIES INC. DIMENSIONS AND DETAILS ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL CUPOLA AND STEEPLE UNITS ARE FABRICATED USING MINIMAL STANDING SEAMS UNLESS OTHERWISE NOTED. ALL CUPOLA AND STEEPLE UNITS ARE DESIGNED TO BE ERECTED ON A COMPLETED ROOFING SYSTEM AND ARE NOT GUARANTEED TO BE LEAK PROOF.

Sheet #

E1F
ELEVATION